

MK-DF

VERTICAL POWER HARROW



MAK FARM[®]
AGRICULTURAL MACHINERY



- MAKFARM VERTICAL POWER HARROW Moving from PTO Strong with hard construction useful a seed row bearing preparing equipment.
- Is easy to use and because of could be produced in various working width dimensions (between 1000mm and 6000mm), can give answer to all farmer needs. The vertical power harrow could be produced as fixed and foldable.
- Is able to processing the soil vertical until 28cm depth that about is not make a ground plate and is not turn the soil upside down and is cure the dust.
- Through the gear roller at the backside (For seeds germination) is preparing a ideal seed bearing and increase a productivity of products.
- Also, with the optional hydraulic attachment all type seed drill (PNEUMATIC and CEREALS) by combination with VERTICAL POWER HARROW and in same time make a soil working and sowing to save time and fuel.



Also, with the optional hydraulic attachment all type seed drill (PNEUMATIC and CEREALS) by combination with VERTICAL POWER HARROW and in same time make a soil working and sowing to save time and fuel.



Through the strong gearbox, is possible to easy and without difficulty to make the preparation process. According the rpm's (540 or 1000) and their power takers of tractors is giving a special gears.



At the backside of the Vertical Power Harrow is placed a rollers. It pressing upper side of soil and help to restructure. Is facilitate to spreading seeds to soil and germination. Percent of the plants of fi eld is increasing. The efficiency of the roller tightening could be gradually adjustable.



Near sides of the machine and moving parts is strong and guarded from part fl oating.



By instantaneous weight changes with the slip shaft system machine couldn't be harmed.



Is owning a long-life blades made of special steel. Blades cloud be changed easily.

MK-DF

VERTICAL POWER HARROW

Model	Tractor Power (hp)	P.T.O. (Rpm)	Working Width (cm)	Blade Number (n.)	Working Depth (cm)	Weight (kg)
						
MK-DF-120/170	60-70	540-1000	175	n.14	8-27	908
MK-DF-120/200	80-90	540-1000	205	n.16	8-27	995
MK-DF-120/250	90-110	540-1000	255	n.20	8-27	1166
MK-DF-120/300	100-120	540-1000	300	n.24	8-27	1320
MK-DF-120/350	100-120	540-1000	350	n.28	8-27	1510
MK-DF-220/300	140-160	750-1000	300	n.24	8-27	1370
MK-DF-220/350	150-170	750-1000	350	n.28	8-27	1565
MK-DF-220/400	170-200	750-1000	400	n.32	8-27	1820
MK-DF-220/450	180-220	750-1000	450	n.36	8-27	2130
MK-DF-220/500	200-240	750-1000	490	n.40	8-27	2417
MK-DF-220/600	220-260	750-1000	585	n.48	8-27	2810



