

SUNGUR

SUBSOILER



MAK FARM
AGRICULTURAL MACHINERY



The SUNGUR Model Subsoiler has been designed to work with low and medium horsepower tractors (70 - 160 Hp). Maximum 50 cm work depth. The feet have a safety system that is protected by a pin and prevents any damage to the feet by cutting the pin. With the double toothed roller system, it is ensured that the cutters are broken down and the soil is leveled and a proper seed bed is prepared. Depth adjustment is made by means of pistons. Machine and soil in the plow depth of the hard layer formed in the cracking and detonation is provided. Thus, in case of wetness problems due to hard layer, late pans are eliminated and early and timely sowing is provided. The aeration of the soil and the water holding capacity of the soil increase. It is easier for the soil to get the deeper nutrients.



DEPTH ADJUSTMENT

Double piston for easy depth adjustment.



DOUBLE GEAR ROLLER

Ideal for soil leveling and cracking.



FOOT SYSTEM

Pin with safety system.

SUNGUR SUBSOILER

Model	Number of Feet	Foot Height (cm)	Work Depth (cm)	Foot Thickness (mm)	Foot Distance (cm)	Working Width (cm)	*Power Requirement (hp)
SGR 5	5	75	50	30	45	250	70-110
SGR 7	7	75	50	30	45	350	100-160

Foot spacing is (cm) : 45

All data are not binding and subject to change without prior notice

* Power requirement may vary depending on soil conditions